



CP185 COMMERCIAL PORTABLE TWO-WAY RADIO

Easy, discreet and prompt communication with your workforce is vital to improving response time, strengthening employee efficiency and increasing customer satisfaction. Motorola's CP185 two-way radios provide a durable, high-quality voice communication solution that helps your business or institution increase productivity and provide excellent customer service.

Ideal for educational institutions, retail and hospitality businesses, service and manufacturing industries and other demanding applications, the Motorola CP185 brings you a robust two-way radio solution. With its extensive feature set—ergonomic shape for comfortable use, voice privacy, and durable, lightweight, compact design—you can enhance communication while increasing efficiency and productivity.

COMPACT DESIGN—easy-to-handle and lightweight.

INCREASED PRIVACY—built-in simple voice scrambling.

HANDS-FREE COMMUNICATION—VOX ready for hands-free use lets users focus immediately on the job at hand.

5 PROGRAMMABLE BUTTONS—enabling easy, one-touch access to up to 10 user-selected features.

MULTI-CHANNEL CAPABILITY—16 channels to support communication among employees and staff members.

X-PAND™ TECHNOLOGY—providing crisp, clear and strong audio quality in noisy environments.

STANDARD LI-ION BATTERY—provides up to 11 hours* of battery life at high power to meet the demands of employee and staff work shifts. A high-capacity battery is available for longer shift requirements and increased communication needs.

RAPID-RATE DROP-IN CHARGING—charge radios in less than 3 hours with the included drop-in charger.

HIGH POWER—adjustable power levels help extend battery life. 5 watt (VHF) / 4 watt (UHF).

INCREASED COVERAGE—Repeater capability when more coverage is required.

TALKAROUND CAPABILITY—enabling communication even when a repeater is not being used.

TIGHTER SPECIFICATIONS—adjacent channel selectivity of -70 dB provides enhanced rejection of interference from strong signals on adjacent channels so messages get through clearly.

MEETS MILITARY STANDARDS 810 C, D, E AND F—to stand up to demanding conditions.

* 5/5/90 duty cycle.

CP185

EDUCATION

HOSPITALITY

MANUFACTURING

PROPERTY MANAGEMENT

RETAIL



PRODUCT SPEC SHEET
CP185™

GENERAL SPECIFICATIONS

	CP185	
	VHF - 136-174 MHz	UHF - 435-480 MHz
Channel Capacity	16	
Channel Spacing	12.5 / 25 kHz switchable	
Model Numbers	AAH03KEF8AA7AN	AAH03RDF8AA7AN
FCC ID	AZ489FT3822	AZ489FT4883
IC ID	109U-89FT3822	109U-89FT4883
FCC Emissions Designators	11K0F3E	16K0F3E
Dimensions (H x W x L)	4.72 x 2.28 x 1.46 inches (120 x 58 x 37 mm)	
Weight (with Li-Ion)	12.34 ounces (350 g)	
Average Battery Life @ 5-5-90% Duty Cycle¹ Li-Ion battery NiMH battery High-Capacity Li-Ion battery	up to 11 hours up to 10 hours up to 16 hours	

TRANSMITTER

	CP185	
	VHF	UHF
RF Output	2 to 5W	2 to 4W
Frequency Stability²	±2.5 ppm	
Spurs and Harmonics	-63dBc (-26dBm @ 5W: -27dBm @ 4W)	
FM Hum and Noise Ratio²	> 40 dB	
Modulation Limiting² (12.5/25 kHz)	≤2.5 kHz / ≤5 kHz	
Audio Response	+ 1 to -3 dB	
Audio Distortion²	< 5%	

RECEIVER

	CP185	
	VHF	UHF
Sensitivity² (12 dB SINAD)	< -119 dBm (.25uV)	
Adjacent Channel Selectivity² (12.5/25 kHz)	-65 dB / -70 dB	
Intermodulation² (12.5/25 kHz)	>70 dB	
Spurious Rejection²	>70 dB	
Audio Distortion²	< 5%	
Hum and Noise Ratio² (12.5/25 kHz)	> 40 dB	
Conducted Emission	< -57 dBm	
Audio Output @ < 5% Distortion	500 mW (at 24 ohm)	

MILITARY STANDARDS—MIL-STD

	810C		810D		810E		810F	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II
High Temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1
Temperature Shock	503.1	—	503.2	I/A1C3	503.3	I/A1C3	503.4	I
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III
Humidity	507.1	II	507.2	II	507.3	II	507.4	—
Salt Fog	509.1	—	509.2	—	509.3	—	509.4	—
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I
Blowing Sand	—	—	510.2	II	510.3	II	510.4	II
Vibration	514.2	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24
Shock	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature Range	-30°C to +60°C (Radio)
Water and Dust Intrusion	IP54, MIL-STD

¹5% receive, 5% transmit, 90% standby.

²All electrical specifications and methods refer to EIA/TIA 603 standards.

Specifications subject to change without notice. All specifications shown are typical.

Radio meets applicable regulatory requirements.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners.



TAB Electronics
72 seven mile Drive
Glendive, Montana 59330
www.tabelect.com
orders@tabelect.com